



CountryMark®

Advantage™

LUBRICANTS

Refining technology with expertise.™

Product Data Sheet

Automatic Transmission Multi-Vehicle Fluid

Description

CountryMark's Advantage™ Multi-Vehicle Automatic Transmission Fluid is specially formulated using synthetic base stocks, seal conditioner, and other performance additives to exceed the performance and protection requirements of newer and rebuilt transmissions. Installers can rely on this single fluid to conveniently and accurately meet a wide array of global OEM requirements in North America. It includes most GM, Ford, Chrysler, Jeep Saturn, Honda/Acura, Toyota, Nissan, Mitsubishi, Hyundai, Mercedes, BMW, VW/Audi, and other transmissions. Always check the owner's manual for details. Strong anti-wear additives provide protection of transmission parts for longer life. In addition, good compatibility with seal material minimizes leaks. It contains a polymer additive that provides shear stability and minimizes oil viscosity change over a wide temperature range.

Features and Benefits

Capability: Formulated to meet the stringent frictional and viscosity requirements of most automatic transmissions from 1983 to the current model year.

Friction Retention: Uniquely balanced frictional properties provide anti-shudder durability, smooth shifting, and precise lockup throughout the service interval.

Operability: Improved cold temperature flow characteristics assure ease of pumping, quick start-up and smooth shifting, even at extremely low temperatures.

Applications

CountryMark Advantage Multi-Vehicle Automatic Transmission Fluids are formulated to meet or exceed engine manufacturers' specifications and requirements.

Exceeds performance requirements:

- Dexron® - III H / Mercon® Fluid
- JASO M315-2004
- Man 339 V1; 339 Z2
- Voith H55.6335 (G607)

Meets performance requirements:

- Mercon® SP and Mercon® LV
- Chrysler ATF+3
- Toyota and Lexus JWS 3309 / Type T III & IV

Also suitable for use in:

- Allison C-4, TES-389
- Caterpillar TO-2
- Nissan & Infinity Matick D/J/K
- Honda and Acura ATF-Z1
- Hyundai KIA SP II / SPIII
- Mazda ATF M-III, ATF M-V
- Audi / VW Part #G 052 025 (09M), 052 990 (09A)
- Mercedes-Benz, Page 236.9/10/11; ATF 3403 M-115
- Land Rover Texaco N402
- Jaguar Idemitsu K17
- Volvo Part #1161540-8
- ZF TE-ML 03D/ 04D/ 09/ 14A/ 14B/ 16L, 17C
- Mercon® V*
- Chrysler ATF+4*
- Allison C-4, TES-295*

* Viscosity requirement is not met

Typical Properties

	TEST	Advantage Multi-Vehicle
Viscosity @ 40°C	D445	34.1
Viscosity @100°C	D445	7.5
Viscosity Index	D2770	150
Brookfield @ -40		cP 9000
API Gravity/Lbs gal		34.1/7.1
Pour Point °C	D97	°F -40
Flash Point		°F 375
Color	Visual	Red

Safety and Health

Caution! Customers are advised to check the oil recommendations for their equipment. Equipment manufacturers recommend specific viscosity grades of oil for certain ambient temperature ranges. Use of oil outside its recommended temperature range can cause lubrication-related problems and lead to permanent engine damage.

CountryMark Advantage™ Lubricants

For additional information contact

Phone: 1-800-537-5303

Dennis Mungle (ext: 4355); Doug Baker (ext: 4315); Jeff Inman (ext: 4314)

www.countrymark.com