



CountryMark®

Advantage™

LUBRICANTS

Refining technology with expertise.™

Product Data Sheet

Extreme Tacky Grease

CountryMark Advantage™ Extreme Tacky Grease is a multi-purpose premium lithium complex grease. This grease has a high dropping point in excess of 500°F, which ensures retention where high temperatures are encountered. The high-quality virgin base fluids provide excellent natural oxidation inhibition. This combined with effective antioxidants as well as corrosion inhibitors provide extra stability under storage and extreme service conditions.



Steel/Factory



Farm Equipment



Construction



Heavy Mobile

Features

Extreme Pressure Performance

Benefits

Exhibits very good extreme-pressure and anti-wear properties for protection and other lubricated mechanisms, including high load-carrying capacity.

Excellent Rust and Corrosion Protection

Excellent lubrication against corrosion, and have excellent resistance to oxidation, which ensures long life in storage and in use.

NLGI Service Classification

Meets (GC-LB) performance requirements for bearing and chassis lubrication.

Applications

Advantage Extreme Tacky Grease covers a wide variety of applications in agriculture, automotive, construction and industrial equipment, such as ball joints, water pumps, universal joints, and hinge points, disc brake wheel bearings, universal joints and conveyor bearings.

Typical Properties

CountryMark Advantage Extreme Tacky Grease

NLGI Grade	#2
NLGI Service	GC-LB
Thickener Type	Lithium Complex
Texture	Tacky
Color	Red
Penetration (worked @ 60 strokes) ASTM D217	265-295
Drop Point °F, ASTM D2265	550
Rust Test, Bearing Corrosion ASTM D1743	Pass
Oxidation Stability, ASTM D942, PSI Drop/100 hrs.	2
Oil Separation, ASTM D 1742, % Loss	1
Wheel Bearing Leakage, ASTM D 1263	2
Water Washout, ASTM D1264, % Loss	2.5 @ 175 °F
Four Ball EP, ASTM D2266, mm Scar D 2266	0.45
Weld, Kg, min.	315
Load Wear Index	50
Timken OK Load, ASTM D 2509, LB	80
Approximate Temperature Range, °F (°C)	-10 to 325 (-23 to 163)
Base Fluid Properties	
cSt @ 40 °C	628
cSt @ 100 °C	41
Viscosity Index	104

Safety and Health

A material safety data sheet is available upon request. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water.

CountryMark Advantage™ Lubricants

For Additional Information Contact

Phone: 1-800-537-5303

www.countrymark.com