



CountryMark®

Advantage™

LUBRICANTS

Refining technology with expertise.™

Product Data Sheet

Multi-Purpose Grease

CountryMark Advantage™ Multi-Purpose Grease is a multi-purpose lithium complex grease. This product has been formulated with a special additive package which ensures high film strength, extreme pressure (EP) and antiwear properties. It has superior water tolerance and resists water washout from chassis points, exhibits good high temperature capabilities and has outstanding mechanical stability by retaining its consistency in hard use.



Construction



General Purpose



Marina



Automotive

Features

Benefits

Extreme Pressure Performance

Very good extreme-pressure and anti-wear properties for protection and other lubricated mechanisms, including high load-carrying capacity.

Excellent Rust and Corrosion Protection

Excellent lubrication against corrosion, and have excellent resistance to oxidation, which ensures long life in storage and in use.

NLGI Service Classification

(GC-LB) performance requirements for bearing and chassis lubrication.

Applications

CountryMark Advantage™ Multi-Purpose Grease performs well in several applications. **For Industrial -** Antifriction bearings, roller and needle bearings, conveyors and run out rolls, crusher bearings, pump bearings and general machinery lubrication. **For Automotive/Equipment -** Chassis points (including ball joints and universal joints), wheel bearings, water pumps, fifth wheels, steering system bearings, kingpins and all construction equipment and agricultural equipment.

Typical Properties	CountryMark Advantage Multi-Purpose Grease
NLGI Grade	#2
NLGI Service	GC-LB
Thickener Type	Lithium Complex
Texture	Smooth/Tacky
Color	Blue
Penetration, (worked @ 60 strokes) ASTM D217	265-295
Drop Point °F, ASTM D2265	500 min
Rust Test, Bearing Corrosion ASTM D1743	Pass
Water Washout, ASTM D1264, 175 °F	5% Max
Four Ball EP, ASTM D2596	
Weld, Kg, min.	315
Load Wear Index	45
Copper Strip Corrosion, ASTM D 4048	1b max.
Timken OK Load, ASTM D 2509	LB 80
Base Fluid Properties	
cSt @ 40 °C	240
cSt @ 100 °C	19.0
Viscosity Index	104

Safety and Health

A material safety data sheet is available upon request. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water.

CountryMark Advantage™ Lubricants

For Additional Information Contact

Phone: 1-800-537-5303

www.countrymark.com